

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### Castable Wax 40 Resin

# SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Product identifier Chinese name: English name: Castable Wax 40 Resin Product code: FLCW4001

# Recommended and limited uses of the product

Relevant identified uses: For use in Formlabs SLA Printers Uses advised against: Not determined or not applicable. Reasons why uses advised against: Not determined or not applicable.

#### Manufacturer or supplier details

Manufacturer: United States Formlabs, Inc 35 Medford St Suite 201 Somerville, MA 02143 +1 617 855 0762 sds@formlabs.com

# **Emergency telephone number:**

United States CHEMTREC

1-800-424-9300 (24/7)

# SECTION 2 HAZARDS IDENTIFICATION

#### Emergency overview

Appearance	Blue Liquid
Odor	Characteristic acrylate
Health Hazards	Causes skin irritation Causes serious eye damage May cause an allergic skin reaction
Safety Hazards	No additional physical hazards.
Environmental Hazards	Toxic to aquatic life with long lasting effects

# GHS hazard categories:

Skin irritation, category 2 Serious eye damage, category 1 Skin sensitization, category 1 Chronic aquatic hazard, category 2

# Label elements

Pictograms:

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### Castable Wax 40 Resin



#### Signal word: Danger

#### Hazard statements:

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H411 Toxic to aquatic life with long lasting effects

# **Precautionary statements:**

#### **Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

- P264 Wash skin thoroughly after handling
- P272 Contaminated work clothing should not be allowed out of the workplace
- P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

# **Response:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P332+P313 If skin irritation occurs: Get medical advice/attention

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P362+P364 Take off contaminated clothing and wash it before reuse

# P391 Collect spillage

# Safe storage: None

# Waste disposal:

P501 Dispose of contents/container in accordance with local/regional/national regulations

#### Other hazards: None known

Physical and Chemical hazards	No additional physical hazards.
Health Hazards	Causes skin irritation Causes serious eye damage May cause an allergic skin reaction
Environmental Hazards	Toxic to aquatic life with long lasting effects

# SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	Weight %	CAS number
Urethane dimethacrylate	35-55	72869-86-4
Acrylic Ester(s)	10-20	Trade Secret

# Additional information: None

# **SECTION 4 FIRST-AID MEASURES**

# **Description of first aid measures**

#### Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. If respiratory

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### Castable Wax 40 Resin

symptoms develop or persist, seek medical advice/attention.

# Skin contact:

Wash affected area with plenty of soap and water. Remove contaminated clothing and launder before reuse. If skin irritation develops or persists, seek medical advice/attention.

# Eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

# Ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

#### Most important symptoms and health effects:

Skin contact may result in redness, pain, burning and inflammation.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Effects are dependent on exposure (dose, concentration, contact time).

#### Advices for first aid responders:

In case of eye contact, seek prompt medical attention while rinsing is continued.

#### Notes for the doctor:

Treat symptomatically.

# SECTION 5 FIRE-FIGHTING MEASURES

#### Extinguishing media

#### Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### Unsuitable extinguishing media:

Do not use water jet.

# Special hazards:

Thermal decomposition may produce irritating/toxic fumes/gases.

#### Firefighting precautions and protective measures:

#### Protective equipment:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

#### Additional information:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

# **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

#### **Environmental precautions:**

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### **Castable Wax 40 Resin**

# Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### Additional advice:

For personal protective equipment see Section 8. For disposal see Section 13.

# SECTION 7 HANDLING AND STORAGE

## Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

#### Storage:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

#### Specific end use(s):

Refer to Section 1 (Recommended Use).

#### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Only those substances with limit values have been included below.

#### **Occupational Exposure limit values:**

No occupational exposure limits noted for the ingredient(s).

#### **Biological limit values:**

No biological exposure limits noted for the ingredient(s).

#### Information on monitoring procedures:

Not determined or not applicable.

#### Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

# Personal protection equipment

#### Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

## Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### **Castable Wax 40 Resin**

standards (or equivalent).

# **Respiratory protection:**

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

# General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance	Blue Liquid
Odor	Characteristic acrylate
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	>100°C
Flash point (closed cup)	>93.5°C
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not Flammable
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	1.01 g/cm3
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	680 cps @ 35°C
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

# Other information

# SECTION 10 STABILITY AND REACTIVITY

#### Reactivity:

Not reactive under recommended handling and storage conditions.

#### Stability:

Stable under recommended handling and storage conditions.

#### Hazardous reactions:

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### **Castable Wax 40 Resin**

Stable under recommended handling and storage conditions.

#### **Conditions to avoid:**

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials. Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

#### Incompatible materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

# Hazardous decomposition:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# SECTION 11 TOXICOLOGICAL INFORMATION

#### Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

# Product data: No data available.

# Substance data:

Name	Route	Result
Urethane dimethacrylate	oral	LD50 Rat: >5000 mg/kg
	dermal	LD50 Rat: >2000 mg/kg

#### Skin corrosion/irritation

#### Assessment:

Causes skin irritation.

# Product data:

# No data available.

# Substance data:

Name	Result
Acrylic Ester(s)	Causes skin irritation.

#### Serious eye damage/irritation

#### Assessment:

Causes serious eye damage.

#### Product data:

No data available.

#### Substance data:

Name	Result
Acrylic Ester(s)	Causes serious eye damage.

#### **Respiratory or skin sensitization**

# Assessment:

May cause an allergic skin reaction.

#### Product data:

No data available.

# Substance data:

Name	Result
Urethane dimethacrylate	May cause an allergic skin reaction.
Acrylic Ester(s)	May cause an allergic skin reaction.

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

#### **Castable Wax 40 Resin**

# Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

# International Agency for Research on Cancer (IARC):

Name	Classification
Urethane dimethacrylate	Not Applicable

National Toxicology Program (NTP): None of the ingredients are listed.

#### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

#### **Reproductive toxicity**

Assessment: Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

# Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

# Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

#### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

#### Information on likely routes of exposure:

No data available.

#### Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

# No data available.

# SECTION 12 ECOLOGICAL INFORMATION

# Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met. Product data: No data available. Substance data:

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

# Castable Wax 40 Resin

	Result
Urethane dimethacrylate	LC50 Danio rerio: 10.1 mg/L (96 h)
	EC50 Daphnia magna: 1.2 mg/L (48 h)
onic (long-term) toxicity	
Assessment:	
Toxic to aquatic life with lo	ng lasting effects.
Product data: No data availa	ble.
Substance data:	
Name	Result
Urethane dimethacrylate	NOEC Desmodesmus subspicatus: 0.2 mg/L (72 h)
Name	Result
Substance data:	Decult
Urethane dimethacrylate	The substance is not readily biodegradable (22% degradation in 28 days
•	
accumulative potential	
•	
Product data: No data availa	ble.
Product data: No data availa Substance data:	
Product data: No data availa	Result
Product data: No data availa Substance data:	
Product data: No data availa Substance data: Name	Result   The substance has moderate potential to adsorb to organic soil and
Product data: No data availa Substance data: Name Urethane dimethacrylate	ResultThe substance has moderate potential to adsorb to organic soil and sediment particles (Log Koc: 3.66).

#### **Product data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:	
Urethane dimethacrylate	This substance is not PBT.
vPvB assessment:	
Urethane dimethacrylate	This substance is not vPvB.

Other adverse effects: No data available.

# SECTION 13 DISPOSAL CONSIDERATIONS

# Waste chemicals:

Do not discharge into public wastewater or surface waters. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

# **Contaminated packages:**

Dispose in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

# **SECTION 14 TRANSPORT INFORMATION**

China GB 6944/12268

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

**Castable Wax 40 Resin** 

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $<5L$ or $<5$ kg

# International Maritime Dangerous Goods (IMDG)

UN number	Un 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer
UN transport hazard class(es)	9
Packing group	III
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $<5L$ or $<5$ kg provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8

# International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 3082
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer
UN transport hazard class(es)	9
Packing group	Ш
Environmental hazards	Marine Pollutant
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5L$ or $5 \leq kg$ provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code		
Bulk Name	None	
Ship type	None	
Pollution category	None	

# SECTION 15 REGULATORY INFORMATION

China regulations

According to GB/T 16483, GB/T 17519

Initial preparation date: 07.14.2021

# **Castable Wax 40 Resin**

**Inventory of Existing Chemical Substances in China (IECSC):** All ingredients are listed or exempt.

**Inventory of Prohibited Chemicals:** None of the ingredients are listed.

Catalog of Hazardous Chemicals: None of the ingredients are listed.

List of Toxic Chemicals Restricted to be Imported and Export in China: None of the ingredients are listed.

List of Hazardous Chemicals for Priority Management - SAWS: None of the ingredients are listed. The Catalog of Priority Hazardous Chemicals for Environment Management (PHCs)-MEP: Not determined

# **SECTION 16 OTHER INFORMATION**

# Abbreviations and Acronyms: None Disclaimer:

This product has been classified in accordance with GB/T 16483-2008, GB 17519-2013 and GB 13690-2009. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains

Initial preparation date: 07.14.2021

with the user.

# End of Safety Data Sheet