

Liqcreate - Tough-X

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: Liqcreate - Tough-X

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Resin for 3D Printing. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Liqcreate Texasdreef 7

3565 CL Utrecht - The Netherlands

Phone.: +31850605849 info@liqcreate.com www.liqcreate.com

1.4 Emergency telephone number: +31850605849 Mo-Fr 8:30-17:00

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning





Hazard statements:

Aguatic Chronic 2: H411 - Toxic to aguatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Precautionary statements:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P391: Collect spillage.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

Contains diisodecyl phenyl phosphite, Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide, Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate, pentaerythritol tetraacrylate.

UFI: RARY-W0VG-A007-U7C2

Date of compilation: 26/01/2021 Version: 1 Page 1/12



Liqcreate - Tough-X

SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification			
CAS: EC:	4986-89-4	pentaerythritol tetraacrylate(1) ATP CLP00				
Index: REACH:	225-644-1 607-122-00-9 Non-applicable	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	30 - <40 %		
CAS:	5888-33-5	Exo-1,7,7-trimethylb	sicyclo[2.2.1]hept-2-yl acrylate(1) Self-classifie	t		
EC: Index: REACH:	227-561-6 607-133-00-9 01-2119957862-25- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	9 - <30 %		
CAS: EC:	75980-60-8	Diphenyl(2,4,6-trime	ethylbenzoyl)phosphine oxide(1) Self-classifie			
EC: 278-355-8 Index: 015-203-00-X REACH: 01-2119972295-29- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Repr. 2: H361f; Skin Sens. 1B: H317 - Warning	2.5 - <3 %			
CAS:	Non-applicable	Acrylated resin(1)	Self-classifie	i		
EC: Index: REACH:	Non-applicable Non-applicable Non-applicable	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	2 - <2.5 %		
CAS: EC:	25550-98-5	diisodecyl phenyl ph	osphite(1) Self-classifie	d ///		
Index:	247-098-3 Non-applicable 01-2119962888-14- XXXX	Regulation 1272/2008	Skin Sens. 1: H317 - Warning	0.1 - <0.5 %		
CAS:	108-95-2	phenol ⁽²⁾	ATP CLP00			
EC: Index: REACH:	203-632-7 604-001-00-2 01-2119471329-32- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B: H314; STOT RE 2: H373 - Danger	<0.01 %		

 $^{^{(1)}}$ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit		
CAS: 108-95-2	% (w/w) >=3: Skin Corr. 1B - H314 1<= % (w/w) <3: Skin Irrit. 2 - H315 % (w/w) >=1: Eye Irrit. 2 - H319		

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:


The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

⁽²⁾ Substance with a Union workplace exposure limit





Liqcreate - Tough-X

SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

Most important symptoms and effects, both acute and delayed: 4.2

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 **Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.


6.3 Methods and material for containment and cleaning up:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections:

See sections 8 and 13.

- CONTINUED ON NEXT PAGE -Date of compilation: 26/01/2021 Version: 1 Page 3/12





Liqcreate - Tough-X

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 15 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occupational exposure limits		
phenol		IOELV (8h)	2 ppm	8 mg/m ³
CAS: 108-95-2	EC: 203-632-7	IOELV (STEL)	4 ppm	16 mg/m ³

DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification	Identification		Local	Systemic	Local	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 5888-33-5	Dermal	Non-applicable	Non-applicable	1,39 mg/kg	Non-applicable	
EC: 227-561-6	Inhalation	Non-applicable	Non-applicable	4,9 mg/m ³	Non-applicable	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 75980-60-8	Dermal	Non-applicable	Non-applicable	0,233 mg/kg	Non-applicable	
EC: 278-355-8	Inhalation	Non-applicable	Non-applicable	0,822 mg/m ³	Non-applicable	
diisodecyl phenyl phosphite	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 25550-98-5	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable	
EC: 247-098-3	Inhalation	Non-applicable	Non-applicable	70,5 mg/m ³	Non-applicable	
phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable	
EC: 203-632-7	Inhalation	Non-applicable	16 mg/m ³	8 mg/m³	Non-applicable	

DNEL (General population):



Liqcreate - Tough-X

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 5888-33-5	Dermal	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
EC: 227-561-6	Inhalation	Non-applicable	Non-applicable	1,45 mg/m ³	Non-applicable	
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	Oral	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable	
CAS: 75980-60-8	Dermal	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable	
EC: 278-355-8	Inhalation	Non-applicable	Non-applicable	0,145 mg/m ³	Non-applicable	
diisodecyl phenyl phosphite	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable	
CAS: 25550-98-5	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable	
EC: 247-098-3	Inhalation	Non-applicable	Non-applicable	35,3 mg/m ³	Non-applicable	
phenol	Oral	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable	
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable	
EC: 203-632-7	Inhalation	Non-applicable	Non-applicable	1,32 mg/m ³	Non-applicable	

PNEC:

Identification				
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	STP	2 mg/L	Fresh water	0,001 mg/L
CAS: 5888-33-5	Soil	0,029 mg/kg	Marine water	0 mg/L
EC: 227-561-6	Intermittent	0,007 mg/L	Sediment (Fresh water)	0,145 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,015 mg/kg
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	STP	Non-applicable	Fresh water	0,0014 mg/L
CAS: 75980-60-8	Soil	0,0222 mg/kg	Marine water	0,00014 mg/L
EC: 278-355-8	Intermittent	0,014 mg/L	Sediment (Fresh water)	0,115 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0115 mg/kg
phenol	STP	2,1 mg/L	Fresh water	0,008 mg/L
CAS: 108-95-2	Soil	0,136 mg/kg	Marine water	0,001 mg/L
EC: 203-632-7	Intermittent	0,031 mg/L	Sediment (Fresh water)	0,091 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.


B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: FFP2)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile)	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+ A1:2010 and EN ISO 374-1:2016+A1:2018

Date of compilation: 26/01/2021 Version: 1 Page 5/12





Liqcreate - Tough-X

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.

F.- Additional emergency measures

Emergency me	asure	Standards	Emergency measure	Standards
		ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 IS <mark>O 3864-1:2011</mark> , ISO 3864-4:2011
Emergency sh	ower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight V.O.C. density at 20 $^{\circ}$ C: 0 kg/m³ (0 g/L)

Average carbon number: 6

Average molecular weight: 94,1 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Liquid

Viscous

Resin

Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:


Vapour pressure at 50 °C:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 26/01/2021 Version: 1 Page 6/12





Liqcreate - Tough-X

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1108,8 kg/m³

Relative density at 20 °C: 1,109

Dynamic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 20 °C: Non-applicable * Kinematic viscosity at 40 °C: >20,5 cSt Concentration: Non-applicable * $\approx 6 - 8$ (at 100 %) Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable *

Solubility in water at 20 °C:

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Heat of combustion:

Flammability (solid, gas):

Non-applicable *

Non-applicable *

Autoignition temperature: 380 °C

Upper flammability limit: Non-applicable *

Explosive:

Lower flammability limit:

Lower explosive limit: Non-applicable *
Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

Non-applicable *

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:


Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

Date of compilation: 26/01/2021 Version: 1 Page 7/12





Liqcreate - Tough-X

SECTION 10: STABILITY AND REACTIVITY (continued)

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: phenol (3); Carbon black (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:



Liqcreate - Tough-X

SECTION 11: TOXICOLOGICAL INFORMATION (continued) Identification Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide CAS: 75980-60-8 EC: 278-355-8 LD50 dermal Non-applicable LC50 inhalation Non-applicable

100 mg/kg

630 mg/kg

Non-applicable

Rat

Rabbit

 EC: 278-355-8
 LC50 inhals

 phenol
 LD50 oral

 CAS: 108-95-2
 LD50 derm

 EC: 203-632-7
 LC50 inhals

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 5888-33-5	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 227-561-6	EC50	>0.1 - 1 mg/L (72 h)		Algae
Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: 75980-60-8	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 278-355-8	EC50	>1 - 10 mg/L (72 h)		Algae
phenol	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
CAS: 108-95-2	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
EC: 203-632-7	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae

12.2 Persistence and degradability:

Identification	De	egradability	Biodegradability	
phenol	BOD5	1,68 g O2/g	Concentration	100 mg/L
CAS: 108-95-2	COD	2,33 g O2/g	Period	14 days
EC: 203-632-7	BOD5/COD	0,72	% Biodegradable	85 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential		
phenol	BCF	17	
CAS: 108-95-2	Pow Log	1.48	
EC: 203-632-7	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
phenol	Koc	50	Henry	2,2E-2 Pa·m³/mol
CAS: 108-95-2		Very High	Dry soil	Yes
EC: 203-632-7	Surface tension	1,847E-2 N/m (231,01 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Date of compilation: 26/01/2021 Version: 1 Page 9/12



Liqcreate - Tough-X

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

14.1 UN number: 14.2 UN proper shipping name:

UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-

1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3 Transport hazard class(es): 9 Labels:

14.4 Packing group: TTT 14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 274, 335, 375, 601

Tunnel restriction code:

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-14.2 UN proper shipping name:

1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3 Transport hazard class(es): 9 Labels:

III 14.4 Packing group: 14.5 Marine pollutant: Yes

14.6 Special precautions for user

Special regulations: 335, 969, 274 F-A, S-F EmS Codes: Physico-Chemical properties: see section 9

Limited quantities: 5 L


Segregation group: Non-applicable 14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:

Date of compilation: 26/01/2021 Version: 1 Page 10/12





Liqcreate - Tough-X

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Exo-

1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3 Transport hazard class(es): 9

Labels:

14.4 Packing group: III **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **Transport in bulk according** Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description		Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:


H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H319: Causes serious eye irritation.

Date of compilation: 26/01/2021 Version: 1 Page 11/12





Liqcreate - Tough-X

SECTION 16: OTHER INFORMATION (continued)

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation. Muta. 2: H341 - Suspected of causing genetic defects. Repr. 2: H361f - Suspected of damaging fertility.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Skin Irrit. 2: Calculation method Skin Sens. 1B: Calculation method Aquatic Chronic 2: Calculation method Eye Irrit. 2: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 26/01/2021 Version: 1 Page 12/12